

KLIMATYZATORY ŚCIENNE

MODEL (jedn. wewn./jedn. zewn.)	Rodzaj czynnika	Moc chłod. [kW]	Moc grzew. [kW]	ZASILANIE V/Ø/Hz	średnica rur przyłączeniowych w mm ciecz/gaz	max długość instalacji/ różnica poziomów w m	Aktualne ceny netto w PLN
RS-7F / RO-7F	R410A	2,25	-	230/1/50	1/4" ; 3/8"	10 5	1830
RS-9F / RO-9F	R410A	2,75	-	230/1/50	1/4" ; 3/8"	15 8	2130
RS-12F / RO-12F	R410A	3,40	-	230/1/50	1/4" ; 3/8"	15 8	2340
RS-14F / RO-14F	R410A	4,20	-	230/1/50	1/4" ; 1/2"	15 8	3720
RS-18F / RO-18F	R410A	5,40	-	230/1/50	1/4" ; 5/8"	20 8	4790
RS-24F / RO-24F	R410A	6,80	-	230/1/50	3/8" ; 5/8"	20 8	5680
RS-30F / RO-30F	R410A	7,90	-	230/1/50	3/8" ; 5/8"	30 15	7210
RS-7U / RO-7U	R410A	2,20	2,30	230/1/50	1/4" ; 3/8"	10 5	1850
RS-9U / RO-9U	R410A	2,60	2,95	230/1/50	1/4" ; 3/8"	15 8	2160
RS-12U / RO-12U	R410A	3,25	3,95	230/1/50	1/4" ; 3/8"	15 8	2360
RS-14U / RO-14U	R410A	4,25	4,80	230/1/50	1/4" ; 1/2"	15 8	3780
RS-18U / RO-18U	R410A	5,40	5,70	230/1/50	1/4" ; 5/8"	20 8	4860
RS-24U / RO-24U	R410A	6,80	7,40	230/1/50	3/8" ; 5/8"	20 8	5740
RS-30U / RO-30U	R410A	7,90	8,40	230/1/50	3/8" ; 5/8"	25 15	7310

KLIMATYZATORY ŚCIENNO-PRZYSUFITOWE

MODEL (jedn. wewn./jedn. zewn.)	Rodzaj czynnika	Moc chłod. [kW]	Moc grzew. [kW]	ZASILANIE V/Ø/Hz	średnica rur przyłączeniowych w mm ciecz/gaz	max długość instalacji/ różnica poziomów w m	Aktualne ceny netto w PLN
RJ-18F / RO-18F	R410A	5,40	-	230/1/50	1/4" ; 5/8"	20 8	4610
RJ-18FA / RO-18FA (A)	R410A	5,40	-	230/1/50	1/4" ; 5/8"	20 8	5550
RJ-24F / RO-24F	R410A	6,80	-	230/1/50	3/8" ; 5/8"	20 8	5910
RJ-30F / RO-30F	R410A	7,90	-	230/1/50	3/8" ; 5/8"	30 15	7420
RJ-14U / RO-14U	R410A	4,20	4,60	230/1/50	1/4" ; 1/2"	15 8	4330
RJ-18U / RO-18U	R410A	5,40	5,70	230/1/50	1/4" ; 5/8"	20 8	5590
RJ-24U / RO-24U	R410A	6,80	7,40	230/1/50	3/8" ; 5/8"	20 8	6430
RJ-30U / RO-30U	R410A	7,90	8,40	230/1/50	3/8" ; 5/8"	25 15	8210

KLIMATYZATORY PRZYSUFITOWE/PODŁOGOWE

MODEL (jedn. wewn./jedn. zewn.)	Rodzaj czynnika	Moc chłod. [kW]	Moc grzew. [kW]	ZASILANIE V/Ø/Hz	średnica rur przyłączeniowych w mm ciecz/gaz	max długość instalacji/ różnica poziomów w m	Aktualne ceny netto w PLN
RY-14F / RO-14F	R410A	4,20	-	230/1/50	1/4" ; 1/2"	15 8	5380
RY-18F / RO-18F	R410A	5,40	-	230/1/50	1/4" ; 5/8"	20 8	5670
RY-24F / RO-24F	R410A	6,50	-	230/1/50	3/8" ; 5/8"	20 8	6280
RY-30F / RO-30F	R410A	8,40	-	230/1/50	3/8" ; 5/8"	30 15	8590
RY-36F / RO-36F (3PH)	R407C/R410A	10,50	-	400/3/50	3/8" ; 5/8"	50 30	10300
RY-45F / RO-45F (3PH)	R407C/R410A	12,70	-	400/3/50	3/8" ; 3/8"	50 30	11390
RY-54F / RO-54F (3PH)	R407C/R410A	14,50	-	400/3/50	3/8" ; 3/4"	50 30	13270
RY-14U / RO-14U	R410A	4,00	4,70	230/1/50	1/4" ; 1/2"	15 8	5590
RY-18U / RO-18U	R410A	5,40	6,00	230/1/50	1/4" ; 5/8"	20 8	6040
RY-24U / RO-24U	R410A	6,50	7,40	230/1/50	3/8" ; 5/8"	20 8	6710
RY-30U / RO-30U	R410A	8,40	9,50	230/1/50	3/8" ; 5/8"	30 15	9120
RY-36U / RO-36U(3PH)	R407C/R410A	10,50	11,00	400/3/50	3/8" ; 5/8"	50 30	11430
RY-45U / RO-45U (3PH)	R407C/R410A	12,70	14,30	400/3/50	3/8" ; 3/4"	50 30	12370
RY-54U / RO-54U (3PH)	R407C/R410A	14,50	16,50	400/3/50	3/8" ; 3/4"	50 30	14200

KLIMATYZATORY MULTISPLIT

MODEL (jedn. wewn./jedn. zewn.)	Rodzaj czynnika	Moc chłod. [kW]	Moc grzew. [kW]	ZASILANIE V/Ø/Hz	średnica rur przyłączeniowych w mm ciecz/gaz	max długość instalacji/ różnica poziomów w m	Aktualne ceny netto w PLN
Dla 2-óch pomieszczeń							
RSW-19F (2 x RS-9F/RO-19F)	R410A	5,50 (2x2,75)	*	230/1/50	1/4" ; 3/8"	15+15 8	6210
RSW-20F (RS-12F+RS-7F/ RO-20F)	R410A	5,70 (3,50+2,2)	*	230/1/50	1/4" ; 3/8"	15+15 8	6830
RSW-24FSS (2 x RS-12F / RO-24FSS)	R410A	7,00 (2x3,50)	*	230/1/50	1/4" ; 3/8"	15+15 8	7250
RSW-24FSU (RS-12F+RC-12F/RO24FSU)	R410A	7,00 (3,50+3,5)	*	230/1/50	1/4" ; 1/2"	15+15 8	8310
RSW-24FUU (2 x RC-12F / RO24FUU)	R410A	7,00 (2x3,50)	*	230/1/50	1/4" ; 3/8"	15 8	9490
Dla 3-ech pomieszczeń							
RSW-20F(3) (3 x RS-9F / RO-20F)	R410A	6,05 (3 x 2,8)	*	230/1/50	1/4" ; 3/8"	15 8	8500
Dla 4-ech pomieszczeń							
RSW-32E(4) (4 x RS-12E / RO-32E)	R407C	9,4 (4x2,35)	*	230/1/50	1/4" ; 1/2"	25, 30 8	13100
Dla 2-óch pomieszczeń							
RSW-19U (2 x RS-9U / RO-19U)	R410A	5,40 (2x2,7)	6,6 (2x3,3)	230/1/50	1/4" ; 3/8"	15+15 8	6600
RSW-20U (RS-12U+RS-7U / RO-20U)	R410A	5,70 (3,45+2,25)	6,70 (4,0)	230/1/50	1/4" ; 3/8"	15+15 8	7120
RSW-24USS (2 x RS-12U / RO-24USS)	R410A	6,90 (2x3,45)	8,0 (2x4,0)	230/1/50	1/4" ; 3/8"	15+15 8	7700
RSW-24USU (RS-12U+RC-12U/RO24USU)	R410A	6,95 (3,45+3,50)	8,0 (2x4,0)	230/1/50	1/4" ; 3/8"	15+15 8	8900
RSW-24UUU (2 x RC-12U / RO24UUU)	R410A	7,00 (2x3,50)	8,0 (2x4,0)	230/1/50	1/4" ; 3/8"	15 8	10230

KLIMATYZATORY KASETONOWE

MODEL (jedn. wewn./jedn. zewn.)	Rodzaj czynnika	Moc chłod. [kW]	Moc grzew. [kW]	ZASILANIE V/Ø/Hz	średnica rur przyłączeniowych w mm cieczech/gaz	max długość instalacji/ różnica poziomów w m	Aktualne ceny netto w PLN
RC-12F / RO-12F	R410A	3,60	-	230/1/50	1/4" ; 3/8"	20 8	5280
RC-14F / RO-14F	R410A	4,10	-	230/1/50	1/4" ; 1/2"	20 8	5730
RC-18F / RO-18F	R410A	5,00	-	230/1/50	1/4" ; 1/2"	20 8	6450
RC-25F / RO-25F	R410A	7,05	-	230/1/50	3/8" ; 5/8"	25 15	7140
RC-30F / RO-30F	R407C/R410A	8,40	-	230/1/50	3/8" ; 5/8"	30 15	9980
RC-36F / RO-36F	R407C/R410A	10,50	-	400/3/50	3/8" ; 5/8"	50 30	11370
RC-45F / RO-45F	R407C/R410A	12,70	-	400/3/50	3/8" ; 3/4"	50 30	12550
RC-54F / RO-54F	R407C/R410A	14,10	-	400/3/50	3/8" ; 3/4"	50 30	14100
RC-12U / RO-12U	R410A	3,55	4,00	230/1/50	1/4" ; 3/8"	20 8	5790
RC-14U / RO-14U	R410A	3,95	4,60	230/1/50	1/4" ; 1/2"	20 8	6180
RC-18U / RO-18U	R410A	4,85	5,40	230/1/50	1/4" ; 1/2"	20 8	6970
RC-25U / RO-25U	R410A	7,00	7,80	230/1/50	3/8" ; 5/8"	25 15	7720
RC-30U / RO-30U	R407C/R410A	8,40	9,50	230/1/50	3/8" ; 5/8"	30 15	10150
RC-36U / RO-36U	R407C/R410A	10,50	11,80	400/3/50	3/8" ; 5/8"	50 30	11710
RC-45U / RO-45U	R407C/R410A	12,70	14,30	400/3/50	3/8" ; 3/4"	50 30	13890
RC-54U / RO-54U	R407C/R410A	14,50	16,40	400/3/50	3/8" ; 3/4"	50 30	15550

KLIMATYZATORY KANAŁOWE

MODEL (jedn. wewn./jedn. zewn.)	Rodzaj czynnika	Moc chłod. [kW]	Moc grzew. [kW]	ZASILANIE V/Ø/Hz	średnica rur przyłączeniowych w mm cieczech/gaz	max długość instalacji/ różnica poziomów w m	Aktualne ceny netto w PLN
RD-7F / RO-7F	R410A	2,15	-	230/1/50	1/4" ; 3/8"	15 8	3560
RD-9F / RO-9F	R410A	2,80	-	230/1/50	1/4" ; 3/8"	15 8	4020
RD-12F / RO-12F	R410A	3,50	-	230/1/50	1/4" ; 3/8"	15 8	4610
RD-14F / RO-14F	R410A	4,20	-	230/1/50	1/4" ; 3/8"	15 8	5110
RD-18F / RO-18F	R410A	5,40	-	230/1/50	1/4" ; 5/8"	20 8	5620
RD-25F / RO-25F	R410A	7,05	-	230/1/50	3/8" ; 5/8"	25 15	7100
RD-30F / RO-30F	R410A	8,40	-	230/1/50	3/8" ; 5/8"	30 15	8420
RD-36F / RO-36F	R410A	10,50	-	400/3/50	3/8" ; 5/8"	50 30	10320
RD-45F / RO-45F	R410A	12,70	-	400/3/50	3/8" ; 3/4"	50 30	11930
RD-60F / RO-60F	R410A	16,50	-	400/3/50	3/8" ; 3/4"	50 30	15550
RD-90E / RO-90E	R407C	25,40	-	380-415/3/50	1/2" ; 1 1/8"	50 30	20210
RD-7U / RO-7U	R410A	2,15	2,45	230/1/50	1/4" ; 3/8"	15 8	4410
RD-9U / RO-9U	R410A	2,70	3,10	230/1/50	1/4" ; 3/8"	15 8	4690
RD-12U / RO-12U	R410A	3,50	4,00	230/1/50	1/4" ; 3/8"	15 8	5440
RD-14U / RO-14U	R410A	4,00	4,70	230/1/50	1/4" ; 1/2"	15 8	5650
RD-18U / RO-18U	R410A	5,40	6,00	230/1/50	1/4" ; 5/8"	20 8	6210
RD-25U / RO-25U	R410A	7,00	7,70	230/1/50	3/8" ; 5/8"	25 15	7450
RD-30U / RO-30U	R410A	8,40	9,50	230/1/50	3/8" ; 5/8"	30 15	9150
RD-36U / RO-36U	R410A	10,50	12,70	400/3/50	3/8" ; 5/8"	50 30	11530
RD-45U / RO-45U	R410A	12,70	14,30	400/3/50	3/8" ; 3/4"	50 30	13020
RD-60U / RO-60U	R410A	16,50	19,50	400/3/50	3/8" ; 3/4"	50 30	16050
RD-90T / RO-90T	R407C	25,40	29,50	380-415/3/50	1/2" ; 1 1/8"	50 30	20810

KLIMATYZATORY OKIENNE

MODEL	Rodzaj czynnika	Moc chłod. [kW]	Moc grzew. [kW]	ZASILANIE V/Ø/Hz	średnica rur przyłączeniowych w mm cieczech/gaz	max długość instalacji/ różnica poziomów w m	Aktualne ceny netto w PLN
RK7F	R410A	2,15	-	230/1/50			1660
RK9F	R410A	2,6	-	230/1/50			1750
RM13F	R410A	3,60	-	220-240/1/50			2310
RF16F	R410A	4,65	-	230/1/50			3440
RK9U	R410A	2,60	2,85	230/1/50			2020
RM12U	R410A	3,45	3,60	230/1/50			2590
RF16U	R410A	4,55	4,30	230/1/50			3830